

## FCW Conversion Recoil Spring Color Codes

- 10# Red      Unit 1 Aluminum Slide with Hi-velocity Ammo
- 9# No Color   Standard Size for Unit 1 Aluminum Slide with Standard Velocity Ammo
- 8# Yellow     Standard Size for Unit 2 with Hi-velocity Ammo  
                  Unit 1 Aluminum Slide with Light Standard Velocity Ammo
- 7# Orange    Unit 1 Steel Slide with Hi-velocity Ammo  
                  Unit 2 with Standard Velocity Ammo
- 6# White     Standard Size for Unit 1 Steel Slide with Standard Velocity Ammo
- 5# Green     Unit 1 Steel Slide with Light Standard Velocity Ammo

The Unit 1 is designed to shoot standard velocity .22lr ammo. It can be tuned for shooting certain high velocity .22lr ammo by changing out the recoil spring to a heavier spring. The Unit 2 is designed to shoot high velocity .22lr ammo. It can be tuned for shooting certain standard velocity .22lr ammo by changing to a lighter recoil spring.

**Shooting your FCW conversion with the incorrect recoil spring can cause an unsafe shooting condition and void the warranty.** Please contact FCW if you have any questions. The color code on springs can wear off over time. If you are unsure of the springs color replace it. Recoil springs should be replaced every 2500-3000 rounds.